

# ECS-125W SERIES

## Intelligent 125 Watt Amplifier

The ECS-125W is an amplifier compatible with the Farenhyt Emergency Communication System. The ECS-125W is used to amplify audio messages for distribution throughout entire facilities.

Since the ECS-125W is designed as a self-contained distributed amplifier, it can be conveniently located near the area of protection to reduce wiring demands. Each ECS-125W is capable of producing 125-watts of audio power. Up to eight ECS-125W amplifiers can be used on the Emergency Communication System. The ECS-125W has its own power supply with battery backup and includes four speaker circuits which can be expanded to eight speaker circuits when used with the optional ECS-CE4. The ECS-125W is fully supervised by the main panel to identify the trouble conditions.

### INSTALLATION

The ECS-125W Series can be surface- or flush-mounted.

### COMPATIBILITY

The ECS-125W Series is compatible with the following Honeywell Farenhyt Series voice evacuation components:

- IFP-300ECS / IFP-300ECSB
- IFP-2100ECS / IFP-2100ECSB



## FEATURES AND BENEFITS

- Complies with UL 864 10th Edition and UL 2572 2nd Edition Standards
- Meets NFPA 72 standards
- Provides SBUS addressable to support up to eight ECS-125W amplifiers per system for a total of 1000 watts
- Each ECS-125W amplifier is supervised and has four onboard audio circuits expandable to eight with the ECS-CE4 expander for a system total of 64 audio circuits
- Uses an easy-to-install wire harness to connect the ECS-CE4 audio circuit expander
- Extends remote installations up to 6,000 feet away from the ECS Series panel
- Includes its own power supply and backup battery
- Selectable for 25V or 70.7V operation
- Available in a red or a black cabinet
- Provides six-wire connection to the ECS System:
  - Two-wires for the voice bus connections
  - Four-wires for the SBUS connections
- Can be surface- or flush-mounted
- Supports 120 VAC or 240 VAC operation

**Honeywell**

Farenhyt Series

# ECS-125W SERIES TECHNICAL SPECIFICATIONS

## PHYSICAL

### Flush Mount Dimensions:

14.05"W x 24.75"H x 3.04"D  
(36.08 W x 62.09 H x 8.07 D cm)

### Overall Dimensions:

16.0"W x 26.25"H x 4.01"D  
(40.06 W x 66.07 H x 10.05 D cm)

**Color:** Red or Black

## ENVIRONMENTAL

**Operating Temperature:** 32°F to 120°F  
(0°C to 49°C)

**Humidity:** 10% to 93% relative humidity  
(non-condensing)

## ELECTRICAL

Module	Voltage	Standby Current	*Alarm Current
ECS-125W/B 25V	120V 60 Hz	300mA	2200mA
ECS-125WHV 25V	240V 50Hz	250mA	1250mA

\*Fully loaded system

### Total Power:

- Circuit 1: 100W max.
- Circuit 2-8: 50W max.

### Main ECS Panel SBUS:

**Standby Current:** 10mA

**Alarm Current:** 10mA

**Battery Charging Capacity:** 7 – 35AH

**Battery Size:** 18AH max. allowed in the cabinet. Use the RBB accessory cabinet for larger batteries up to 35AH per system.

### Voice Integration Wiring:

- Six conductor
- Two voice bus
- Four SBUS

## ORDERING INFORMATION

**ECS-125W:** Intelligent 125W Amplifier, red

**ECS-125WB:** Intelligent 125W Amplifier, black

**ECS-125WHV:** High Voltage (240V) 125W Amplifier

## ACCESSORIES

**ECS-CE4:** Audio Circuit Expander

**RBB:** Remote Battery Box accessory cabinet. Use for backup batteries up to 35AH and batteries too large to fit into an ECS-50W cabinet.**SK-SCK:** Seismic Compliance Kit

## STANDARDS AND CODES

The ECS-125W Series complies with the following standards and codes.

- UL 864, 10th Edition: Standard for Control Units for Fire Alarm Systems
- UL 864, Local Protective Signaling Systems
- UL 2572, 2nd Edition: Standard for Mass Notification Systems
- UL 1711
- NFPA:
  - NFPA 13
  - NFPA 70
  - NFPA 72

## AGENCY LISTINGS AND APPROVALS

- UL Listed: S2766
- CSFM Approved: 7300-0559:0173
- FDNY: Approved

Farenhyt™ is a trademark, and Honeywell® is a registered trademark of Honeywell International, Inc.

This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

Country of origin: U.S.A.

## Honeywell Fire Solutions

12 Clintonville Road  
Northford, CT 06472-1610  
203.484.7161  
www.farenhyt.com

350772 | G | 04-22  
©2022 Honeywell International Inc.

THE  
FUTURE  
IS  
WHAT  
WE  
MAKE IT

Honeywell